

AFM42 SERIES ALL-FLEX MOWER

HP REQUIRED
40-70 HP

HITCH
Pull-Type




Get the results you deserve!

The AFM42 Series is perfect for golf course maintenance, large estates, city recreation areas and sports fields. Sleek enough to get under trees and agile enough to turn on a dime, the AFM42 Series is just right for all around turf maintenance. And the quality of cut is the best feature of all.



Over center release easily takes tension off the drive belts during extended off time, or for belt replacement.

5 YEAR
LIMITED GEARBOX
WARRANTY



Anti-scalp rollers on nose and trailing edges of decks protect the deck as well as the turf.



Optional Hydraulic Wing Unlock allows user to unlock the wings from the tractor seat.



Low deck pivot allows for greater side to side flotation on the wing decks.

	AFM4214	AFM4216
Horsepower	40-70 HP	
Hitch	Pull-Type, Adjustable Clevis & Safety Tow Chain	
Working Width (cm)	14' (427)	16' 8" (508)
Overall Width	14' 3"	16' 10"
Transport Width	7' 11"	8' 5"
Positive Tongue Wt - lb	540	580
Weight - lb (kg) (w/15" tires)	3,000 (1,361)	3,315 (1,504)
Cutting Height	3/4" - 5-1/4" in 1/4" Incr.	
Wing Cylinders	2-1/2" x 12"	
Rear Deck Cylinder	2-1/2" x 8"	
Gearbox	540 RPM, 3 Wing, 1 Splitter	
Decks: 3 each	60"	72"
Deck Thickness	3/16"	
Deck Overlap	6"	8"
Deck Spindle Housing	Cast Iron Greaseable Hubs	
Blade Size	5/16" x 2-1/2" x 20-29/32"	5/16" x 2-1/2" x 25"
Blade Overlap	1-1/4"	
Blade Tip Speed	18,396 fpm	18,340 fpm
Blade Bearings	Greaseable Ball Bearings	
Blade Spindles	1-3/8" Stressproof® Shaft	
Blade Spindle RPM	3,362 RPM	2,802 RPM
Drive Train	540 RPM B-Section V Belt	
Discharge	Rear	
Deck Tires - 10 total	15 x 6.6 Air Tire, Sealant or 18 x 9.5 Air Tire, Sealant	
Deck Wheel Spindles	1-1/4" w/Nylon Bushings	
Transport Tires and Bearing	23 x 10.5, Sealant Tapered Bearings	
Anti-Scalp Roller	Front Center and Outside Deck Corners	
Input Driveline	Cat. 4 CV w/Slip Clutch	
Deck Driveline	Cat. 3	
Mowing capacity @2mph	3.39 Acres/hr	4.0 Acres/hr
@4mph	6.78 Acres/hr	8.1 Acres/hr
@6mph	10.17 Acres/hr	12.1 Acres/hr
Flex - Wings	23° L-R, 22° F-B	
Flex - Center	10° L-R, 22° F-B	
Transport Lights	Standard	
Colors		

MOWERS

*See dealer for complete warranty information.