

MODEL	P-503	P-505	P-508-3S	P-509-60	P-510/3S	P-511-60	P-516	P-516/3S	P-524
Gross vehicle weight rating	1.5 tons	2.5 tons	4 tons <sup>1</sup>	4 tons <sup>1</sup>	5 tons	5 tons	8 tons <sup>1</sup>	8 tons <sup>1</sup>	12 tons <sup>2</sup>
Interior box dimensions	50 1/2" x 69 1/2"	60" x 94"	62" x 99"	71" x 105"	62" x 99"	71" x 105"	55 5/8" x 117 1/2"	90" x 120"	84" x 138"
Bed thickness	12G	3/16"	3/16"	3/16"	3/16"	3/16"	3/16"	3/16"	3/16"
Side panels	12" x 12G	14" x 12G	14" x 12G	14" x 12G	14" x 12G	14" x 12G	16" x 12G	16" x 12G	24" x 12G
Front / back panel	12 1/4" x 12G	19" x 12G	19" x 12G	19" x 12G	19" x 12G	19" x 12G	24" x 12G	24" x 12G	32" x 12G
Removable panels	4	4	4	4	4	4	4	4	4
Rear panel opening	From top or bottom	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Platform height	22"	29 1/2"	35 1/2"	35 1/2"	35 1/2"	35 1/2"	32"	36 1/2"	39"
Overall length	106"	139"	143"	147"	143"	147"	166"	177"	200 1/2"
Overall width	54"	64"	68"	77"	68"	77"	86"	97"	91"
Overall height	36"	52 1/2"	60"	60"	60"	60"	62"	65"	72"
Free height at maximum tilt	10"	15"	20"	14"	20"	14"	15"	20"	20"
Total height at maximum tilt	72"	103"	117"	108"	117"	108"	122"	130"	154"
Tread width center/center	36 1/4"	53 1/4"	51"	60"	51"	60"	75 1/2"	75"	72 1/2"
Dumping angle (back)	47°	47°	47°	47°	47°	47°	47°	47°	47°
Dumping angle (2 sides)	N/A	N/A	47°	N/A	47°	N/A	N/A	47°	N/A
Grain door	N/A	N/A	Option	Option	Option	Option	Option	Option	Included
Axle	Tandem	Tandem	Single	Single	Tandem	Tandem	Tandem	Tandem	Tandem
Hubs	4 bolts	5 bolts	6 bolts	6 bolts	6 bolts	6 bolts	6 bolts	6 bolts	8 bolts
Hub capacity	1000 lbs	2500 lbs	5000 lbs	5000 lbs	4000 lbs	4000 lbs	5000 lbs	5000 lbs	5000 lbs
Spindle diameter	1 1/4"	2"	2 1/4"	2 1/4"	2"	2"	2 1/4"	2 1/4"	2 1/4"
Number of bolts (wheels)	4	4	2	2	4	4	4	4	4
Wheels dimensions	8.5" x 8"	12" x 8.5"	15" x 8"	15" x 8"	15" x 8"	15" x 8"	15" x 8"	15" x 8"	15" x 10"
Included tires	12 x 14 x 8"	Turf-Saver 23 x 10.5 x 12"	11L15 (8 ply)	11L15 (8 ply)	11L15 (8 ply)	11L15 (8 ply)	11L15 (8 plis)	11L15 (8 ply)	12.5L15 (10 ply)
Optional tires		Multi Trac 23 x 10.5 x 12"	11L15F1 (D)	11L15F1 (D)			11L15F1 (D)	11L15F1 (D)	12.5L15F1 (F)
Hitch : clevis/swivel	Included	Inclus	Included	Inclus	Included	Included	12.5L15 (10 ply)	12.5L15 (10 ply)	
Jack	Included	Included	Inclus	Inclus	Inclus	Included	Included	Included	Inclus
Oil volume required			5 l		5 l		Included	Included	Inclus
Cylinder(s)	1 double acting	1 double acting	1 single acting	1 double acting	1 single acting	1 double acting	2 double acting	1 single acting	1 single acting
Total weight	640 lbs / 290 kg	1560 lbs / 708 kg	1840 lbs /835 kg	1725 lbs / 782 kg	2100 lbs / 953 kg	2060 lbs / 934 kg	2245 lbs / 1018 kg	3040 lbs / 1379 kg	4195 lbs / 1903 kg